

hyperref package options

Sebastian Rahtz et. al.

September 4th 2006

| | | |
|--------------------|---|-------------------------|
| a4paper | use A4 paper | |
| a5paper | use A5 paper | |
| anchorcolor | set color of anchors | black |
| b5paper | use B5 paper | |
| backref | do bibliographical back references | false |
| baseurl | set base URL for document | <i>empty</i> |
| bookmarks | make bookmarks | true |
| bookmarksnumbered | put section numbers in bookmarks | false |
| bookmarksopen | open up bookmark tree | false |
| bookmarksopenlevel | level to which bookmarks are open | \maxdimen |
| bookmarkstype | to specify which ‘toc’ file to mimic | toc |
| breaklinks | allow links to break over lines | false |
| citebordercolor | color of border around cites | 0 1 0 |
| citecolor | color of citation links | green |
| colorlinks | color links | false |
| | | true (tex4ht, dviwindo) |
| debug | provide details of anchors defined same as verbose | false |
| draft | do not do any hyper linking | false |
| dvipdf | use dvipdf backend | |
| dvipdfm | use dvipdfm backend | |
| dvipdfmx | use dvipdfmx backend | |
| dvips | use dvips backend | |
| dvipsone | use dvipsone backend | |
| dviwindo | use dviwindo backend | |
| encap | to set encap character for hyperindex | |
| executivepaper | use executivepaper | |
| extension | suffix of linked files | dvi |
| filebordercolor | color of border around file links | 0 .5 .5 |
| filecolor | color of file links | cyan |
| final | opposite of option draft | true |
| frenchlinks | use small caps instead of color for links | false |
| hyperfigures | make figures hyper links | false |
| hyperfootnotes | set up hyperlinked footnotes | true |
| hyperindex | set up hyperlinked indices | true |
| hypertex | use HyperTeX backend | |
| hypertextnames | use guessable names for links | true |
| implicit | redefine L ^A T _E X internals | true |
| latex2html | use L ^A T _E X2HTML backend | |
| legalpaper | use legalpaper | |
| letterpaper | use letterpaper | |
| linkbordercolor | color of border around links | 1 0 0 |
| linkcolor | color of links | red |

| | | |
|--------------------------|--|-----------------------------|
| linktocpage | make page number, not text, be link on TOC, LOF and LOT | false |
| menubordercolor | color of border around menu links | 1 0 0 |
| menucolor | color for menu links | red |
| naturalnames | use L ^A T _E X-computed names for links | false |
| nesting | allow nesting of links | false |
| pageanchor | put an anchor on every page | true |
| pagebackref | backreference by page number | false |
| pagebordercolor | color of border around page links | 1 1 0 |
| pagecolor | color of page links | red |
| pdfauthor | text for PDF Author field | <i>empty</i> |
| pdfborder | width of PDF link border | 0 0 1 |
| | | 0 0 0 (colorlinks) |
| pdfcenterwindow | position the document window center of the screen | false |
| pdfcreator | text for PDF Creator field | LaTeX with hyperref package |
| pdfdirection | direction setting | <i>empty</i> |
| pdfdisplaydoctitle | display document title instead of file name in title bar | false |
| pdfduplex | paper handling option for print dialog | <i>empty</i> |
| pdfffitwindow | resize document window to fit document size | false |
| pdfhighlight | set highlighting of PDF links | /I |
| pdfkeywords | text for PDF Keywords field | <i>empty</i> |
| pdflang | PDF language identifier (RFC 3066) | <i>empty</i> |
| pdfmenubar | make PDF viewer's menu bar visible | true |
| pdfnewwindow | make links that open another PDF file start a new window | false |
| pdfnonfullscreenpagemode | page mode setting on exiting full-screen mode | <i>empty</i> |
| pdfnumcopies | number of printed copies | <i>empty</i> |
| pdfpagelayout | set layout of PDF pages | <i>empty</i> |
| pdfpagemode | set default mode of PDF display | <i>empty</i> |
| pdfpagelabels | set PDF page labels | false |
| pdfpagescrop | set crop size of PDF document | <i>empty</i> |
| pdfpagetransition | set PDF page transition style | <i>empty</i> |
| pdfpicktrackbypdfsize | set option for print dialog | <i>empty</i> |
| pdfprintarea | set /PrintArea of viewer preferences | <i>empty</i> |
| pdfprintclip | set /PrintClip of viewer preferences | <i>empty</i> |
| pdfprintpagerange | set /PrintPageRange of viewer preferences | <i>empty</i> |
| pdfprintscaling | page scaling option for print dialog | <i>empty</i> |
| pdfproducer | text for PDF Producer field | <i>empty</i> |
| pdfstartpage | page at which PDF document opens | 1 |
| pdfstartview | starting view of PDF document | /Fit |
| pdfsubject | text for PDF Subject field | <i>empty</i> |
| pdftex | use pdfT _E X backend | |
| pdftitle | text for PDF Title field | <i>empty</i> |
| pdftoolbar | make PDF toolbar visible | true |
| pdfview | PDF 'view' when on link traversal | <i>empty</i> |
| pdfviewarea | set /ViewArea of viewer preferences | <i>empty</i> |
| pdfviewclip | set /ViewClip of viewer preferences | <i>empty</i> |
| pdfwindowui | make PDF user interface elements visible | true |
| plainpages | do page number anchors as plain arabic | true |
| ps2pdf | use ps2pdf backend | |
| raiselinks | raise up links (for HyperTeX backend) | false |

| | | |
|----------------|--|---------|
| runbordercolor | color of border around ‘run’ links | 0 .7 .7 |
| setpagesize | set page size by special driver commands | true |
| tex4ht | use T _E X4ht backend | |
| textures | use Textures backend | |
| unicode | Unicode encoded pdf strings | |
| urlbordercolor | color of border around URL links | 0 1 1 |
| urlcolor | color of URL links | magenta |
| verbose | be chatty | false |
| vtex | use V _T E _X backend | |
| vtexpdfmark | use backend for V _T E _X in PDF/PS mode (pdf-mark specials) | |
| xetex | use XeT _E X backend | |
